

Power Supply PS/2 AC Input ATX Type

ACE-841AP-S

400W



PFC



Input Type	90 ~ 264VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	28A (0.2A min)	33A (4A min)	20A (0.5A min)	0.5A	1A	2A
Efficiency	70%					
Temperature	0 ~ 50°C (Operating), -20 ~ 80°C(Storage)					
MTBF(hrs)	100,000					
Output Connector	20+4PIN ATX x1, 4PIN 12V CPU x1, HDD/CDROM x5, FDD x2, SATA x2, Extra +5V(P10) x1					

Ordering Information

ACE-841AP-S-RS 400W AC-DC PS/2 ATX Power Supply, with PFC & on/off switch

ACE-840A

400W



Input Type	95 ~ 132VAC, 180 ~ 264VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	28A (0.2A min)	40A (2A min)	15A (0.2A min)	0.3A	0.8A	2A
Efficiency	65%					
Temperature	0 ~ 50°C (Operating), -20 ~ 65°C(Storage)					
MTBF(hrs)	100,000					
Output Connector	20PIN ATX x1, 4PIN 12V CPU x1, HDD/CDROM x8, FDD x2, Extra +5V(P10) x1					

Ordering Information

ACE-840A-RS 400W AC-DC PS/2 ATX Power Supply, AC select switch

ACE-832AP

300W



PFC



Input Type	90 ~ 264VAC Full Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	28A (0.3Amin)	30A (0.1A min)	15A	0.3A	0.8A	2A
Efficiency	65%					
Temperature	0 ~ 50°C (Operating), -20 ~ 80°C(Storage)					
MTBF(hrs)	50,000					
Output Connector	20PIN ATX x1, 4PIN 12V CPU x1, HDD/CDROM x8, FDD x2, Extra +5V(P10) x1					

Ordering Information

ACE-832AP-RS 300W AC-DC PS/2 ATX Power Supply, with PFC

ACE-832AP-S-RS 300W AC-DC PS/2 ATX Power Supply, with PFC & on/off switch

ACE-832A

300W



Input Type	95 ~ 132VAC, 180 ~ 264VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	28A (0.3Amin)	30A (0.1A min)	15A	0.3A	0.8A	2A
Efficiency	65%					
Temperature	0 ~ 50°C (Operating), -20 ~ 65°C(Storage)					
MTBF(hrs)	100,000					
Output Connector	20PIN ATX x1, 4PIN 12V CPU x1, HDD/CDROM x8, FDD x2, Extra +5V(P10) x1					

Ordering Information

ACE-828A-RS 300W AC-DC PS/2 ATX Power Supply

ACE-828A

280W



Input Type	90 ~ 130VAC, 180 ~ 260VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	8A	25A (2A min)	10A (0.1A min)	0.5A	0.5A	0.72A
Efficiency	65%					
Temperature	Operating : -20 ~ 70°C (40 ~ 70°C derating curve) Storage : -40 ~ 75°C					
MTBF(hrs)	110,000					
Output Connector	20PIN ATX x1, HDD/CDROM x5, FDD x2					

Ordering Information

ACE-828A-RS 280W AC-DC PS/2 ATX Power Supply

ACE-828M

Medical 280W



Input Type	90 ~ 130VAC, 180 ~ 260VAC Auto Range					
Output Voltage	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	8A	25A (2A min)	10A (0.1A min)	0.5A	0.5A	0.72A
Efficiency	65%					
Temperature	Operating : -20 ~ 70°C (40 ~ 70°C derating curve) Storage : -40 ~ 75°C					
MTBF(hrs)	170,000					
Output Connector	20PIN ATX x1, HDD/CDROM x5, FDD x2					

Ordering Information

ACE-828M-RS 280W AC-DC PS/2 ATX Power Supply, meet Medical standard