

# Power Supply PS/2 AC Input AT Type

## ACE-932A

**300W**



### Specifications

Input Type	85 ~ 130 VAC, 180 ~ 265 VAC Auto Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
	33A (3 A min)		8A (0.2 A min)	0.5 A	3 A	
Efficiency	68 %					
Temperature	Operating : 0 °C ~ 50 °C (50 °C ~ 70 °C derating curve) Storage : -40 °C ~ 75 °C					
MTBF(hrs)	120,000					
Output Connector	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x4, FDD x2					

### Ordering Information

Part No.	Description
ACE-932A-S-RS	300 W AC-DC PS/2 AT Power Supply

## ACE-925A/AP

**200W**



**PFC**



### Specifications

Input Type	85 ~ 265VAC Full Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
	22 A (1A min)		7 A (0.1A min)	0.5 A	0.7 A	
Efficiency	68 %					
Temperature	0 °C ~ 50 °C (Operating), -40 °C ~ 75 °C (Storage)					
MTBF(hrs)	130,000 (ACE-925A), 140,000 (ACE-925AP)					
Output Connector	P8+P9 x1, HDD/CDROM x5, FDD x2					

### Ordering Information

Part No.	Description
ACE-925A-RS	200 W AC-DC PS/2 AT Power Supply
ACE-925AP-RS	200 W AC-DC PS/2 AT Power Supply, with PFC

## ACE-925M

**200W**

**Medical**



### Specifications

Input Type	90 ~ 264VAC Full Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
	22 A (4A min)		7 A (1A min)	0.5 A	0.5 A	
Efficiency	65 %					
Temperature	Operating : 0 °C ~ 70 °C (40 °C ~ 70 °C derating curve) Storage : -40 °C ~ 75 °C					
MTBF(hrs)	110,000					
Output Connector	P8+P9 x1, HDD/CDROM x5, FDD x2					

### Ordering Information

Part No.	Description
ACE-925M-RS	200 W AC-DC PS/2 AT Power Supply, meet Medical standard

## ACE-920A

**150W**



### Specifications

Input Type	85 ~ 265VAC Full Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
	20 A (1A min)		4 A (0.1A min)	0.5 A	0.5 A	
Efficiency	68 %					
Temperature	0 ~ 50 °C (Operating), -40 °C ~ 75 °C (Storage)					
MTBF(hrs)	160,000					
Output Connector	P8+P9 x1, HDD/CDROM x3, FDD x2					

### Ordering Information

Part No.	Description
ACE-920A-RS	150 W AC-DC PS/2 AT Power Supply